3408



Gusset Sleeve









Patron Saint® Flame Retardant ARC Rated Closed Front Shirt with "X" Back LOXY F/R R/tape - L/S

Fabric: 190gsm cotton drill

Closed front concealed placket with FR plastic studs closure, Gusset sleeve, comply with BS EN ISO 116612:2008 for FR & NFPA70E(ASTEMF1959/F) for Arc rating - APTV: 6.8Cal/CM2, HRC:1. "X" back with additional tape on back pattern LOXY Sto-nor 9801 FR Reflective tape. L/S. NSW Rail complaint.

Size: XS-6XL

Colour:

FEATURES:



SUN Protection UPF 40+ - 50+

DNC garments are tested for UPF (ultraviolet protection factor) in accordance with AS 4399:2020. The level of protection varies depending on the fabric and colour of the garment. 15+ good protection, 30+ / 35+ very good protection, 40+ / 50+ excellent protection.



Hi-Vis D/N Fabric & Design AS/NZS 4602.1:2024

DNC Hi-Vis garments are manufactured to comply with new Hi-Vis standard Class F AS/NZS1906.4:2023, Class D/N, AS/NZS 4602.1:2024 to meet the requirements of Hi-Vis safety standards Hi-Vis Fabric & Design of garments, for day and night use.



100% Cotton

DNC has an extensive 100% cotton range for a natural feeling garment with Anti-Static and Electrical Protection features.



Arc-Rates Flame Resistant Patron Saint®

DNC Patron Saint® flame retardant range complies with Class EN ISO11612. Also EEC Standards, EN470-1, EN531. For more information please visit www.xxhyhs.com.



Carbon grid Anti-Static

The latest technology is used in the production of DNC Flame Resistant and Carbon grid 280gsm “3 layer bonded into 1” 99% Polyester/PU, 1% Anti-Static Carbon, breathable waterproof & inherent FR fabric rain jacket & pants, comply with EN ISO 14116:2008 for FR & BS EN1149-5:2008 for Anti-Static. DNC cotton garments containing no metal buttons/zip are also classified under Anti-Static garments.



Electrical Protection

DNC cotton made garments containing no metal buttons or zippers and are suitable for use in electrical or gas trades.



LOXY 9801 FR Reflective Tape

DNC use premium LOXY Sto-nor 9801 Flame Resistant (FR) Tape through our Flame Resistant Range. LOXY Sto-nor 9801 FR Tape – Industrial wash 50 cycles @60C. Complies with ISO14116/FR, NFPA2112/FR; EN 1149-3/Anti-Static, AS/ NZS1906.4/HiVis. Standard.