3782

HiVis D/N 2 Tone Drill Shirt with H Pattern CSR R/ Tape - Long Sleeve



Fabric: 190gsm 100% Cotton
Full open front, twin button down flap chest pocket, two tone front & back. Under arm & type 2 (part-mesh) vertical back cotton mesh vents. Gusset Sleeve. Hoop pattern CSR Reflective Tape.

Size: XS-6XL

Colour:

FEATURES:

SUN Protection UPF 40+ - 50+
DNC garments are tested for UPF (ultraviolet protection factor) in accordance with AS 4399:2020. The level of protection varies depending on the fabric and colour of the garment. 15+ good protection, 30+ / 35+ very good protection, 40+ / 50+ excellent protection.

Hi-Vis Fabric & Material Only AS/NZS 1906.4:2023
DNC Hi-Vis fabric and material of garments manufactured to comply with Hi-Vis standard Class F AS/NZS1906.4:2023.

CSR Reflective Tape
Alternatively DNC also use premium quality Reflective Tape for the value Hi-Vis range. CSR Reflective Tape fully complies with AS/NZS1906.4:2010 for Hi-Vis material. Home wash 50 Cycles @ 60°C.

100% Cotton
DNC has an extensive 100% cotton range for a natural feeling garment with Anti-Static and Electrical Protection features.

COOL- BREEZE Airflow Vents
DNC Cool-Breeze airflow cooling system removes sweat and body heat through innovative under-arm vents, upper back, or vertical vents.

Anti-Static
The latest technology is used in the production of DNC Carbon Grid Anti-Static jacket and pants, complies BS EN 1149-5:2018. DNC cotton garments containing no metal buttons or zippers are also classified under DNC Anti-Static.

Electrical Protection
DNC cotton made garments containing no metal buttons or zippers and are suitable for use in electrical or gas trades.

Environmentally Friendly Green Dye Oeko-Tex Standard 100 Safe to wear against the skin
All DNC garments use the Green Dye only, except for the Patrol Saint Flame Retardant range. All DNC garment fabric fully complies with Oeko-Tex standard 100 Class II for products with direct contact to the skin in which prohibited to use aromatic amines, sensitizing dyes and cancer risk dyes. Green Dye should meet the following conditions: Does not contain harmful or non-aromatic amine; dye itself, non-carcinogenic, sensitization, acute toxicity; the use of formaldehyde and, after extraction of heavy metals in the following limits; non-environmental hormone; non persistent organic pollutants; does not produce pollution of the environment harmful chemicals; not produce chemicals that pollute the environment; colour fastness and superior to disable the use of dyes.